




TP070

TORNEIRA EMBUTIR LAVAT.TEMPORIZ.
PAREDE REG. 6/15 SEG. 3BAR







A S M T A P S[®]

W A T E R S O U L

EN CONCEALED SELF CLOSING WASHBASIN
TAP TIM. 6 SEG./3 BAR

FR ROBINET TEMPORISÉ LAVABO
ENCASTRÉE RÉG.6 SEG./3 BAR

ES GRIFO LAVABO TEMPORIZADO EMPOTRAR
REG.6 SEG./3 BAR



TP070 Rev. A 07/05/2025

CARACTERÍSTICAS TÉCNICAS

PRESSÃO RECOMENDADA: RECOMMENDED PRESSURE:	3 - 4 BAR
TEMPERATURA RECOMENDADA: RECOMMENDED TEMPERATURE:	15°C - 65°C
MATERIAIS: MATERIALS:	Latão
TEMPERATURA MÁXIMA: MAXIMUM TEMPERATURE:	70°C
CAUDAL MÁXIMO A 3 BAR: MAXIMUM FLOW AT 3 BAR:	5L/MIN
LIGAÇÃO DE ENTRADA: INPUT CONNECTION:	G1/2"
LIGAÇÃO DE SÉIDA: OUTPUT CONNECTION:	G1/2"
PESO (KG): WEIGHT (KG):	1,85
DIMENSÕES EMBALAGEM (MM): SIZE PACKAGING (MM):	274x162x102

ACABAMENTOS

CR - CROMADO CHROME CHROME CROMO
PR - PRETO MATE BLACK MATT NOIR MAT NEGRO MATE
BR - BRANCO MATE WHITE MATT BLANC MAT BLANCO MATE
ST - SATINOX SATINOX SATINOX SATINOX
AT - ANTRACITE ANTHRACITE ANTHRACITE ANTRACITA
GM - GUNMETAL GUNMETAL GUNMETAL GUNMETAL
GMM - GUNMETAL MATE GUNMETAL MATT GUNMETAL MAT GUNMETAL MATE
OR - DOURADO GOLD DORÉ DORADO
ORM - DOURADO MATE GOLD MATT DORÉ MAT DORADO MATE
CB - COBRE COPPER CUIVRE COBRE
CBM - COBRE MAT COPPER MAT CUIVRE MAT COBRE MATE

TECNOLOGIA

	Temporizada Regulável Temporized
	Cartucho Com Regulação De Caudal Cartridge With Flow Control
	Embutido a parede Built-in to wall
.	.
.	.
.	.
.	.
.	.
.	.
.	.